

Technical data sheet

M-iClean UM+

M007DWUC10M3-30

Execution for: Serbia

Dishwashing machine

3-phase current: 3N PE 400V 50Hz

Fresh water line: Soft cold water 0-3 °dH



© MEIKO 2019

Sample illustration

Technical data

Rack capacity/h (theoretical)	40 / 30 / 15 racks/h
Programme cycle time	90 / 120 / 240 s
Rack dimension	500 x 500 mm
Entry height	435 mm
Dimensions (W x Hmin x D)	600 x 820 x 600 mm
Electrical feeding cable	3-phase current: 3N PE 400V 50Hz nominal capacity: 6,7 kW nominal current: 15,5 A
Local fuse protection	16 A
Protection class of the machine	IP X4
Equipment	Control system MIKE CPU4 Bluetooth interface for wireless communication Leakage detector Boiler safety device Automatic self-cleaning when tank is drained connecting kit 1,8 m
Fresh water line	Air gap 'AB' in accordance with EN 1717 with booster pump
Fresh water supply	Minimum flow pressure 60 kPa / 0,6 bar in front of solenoid valve Maximum pressure: 500 kPa / 5,0 bar Max. supply water temperature 60 °C
Flow rate	3 l/min
Final rinse water quantity	2,4 liters/cycle, variable
Boiler	Contents: 7,9 l Heater: 6,00 kW Temperature: 83 °C Tank / boiler locked

Technical data sheet

Wash tank	Filling: 11,0 l Heater: 2,00 kW Temperature: 60 °C
Wash pump, with frequency converter	Performance: 0,40 kW
Dosing of rinse aid	Hose pump (24 V) with time control and suction lance
Detergent dosage	Hose pump (24 V) with time control and suction lance
Material	Cladding: 1.4301 Wash tank: 1.4301 Boiler: 1.4571
Heat emission	for 20 programme cycles/h total: 2,1 kW perceptible: 1,4 kW latent: 0,7 kW
Ventilation flow rate	540 m³/h
Steam emission	1,0 kg/h
Emission sound pressure level at the workplace (LpA)	61 dB
Net / gross weight	74,0 kg / 86,0 kg (standard packaging)
Packaging dimensions (W x H x D)	700 x 1050 x 700 mm (standard packaging)