

# Technical data sheet

## UPster H 500

Execution for: Hong Kong

Country of production: China

Hood type dishwashing machine

3-phase current: 3N PE 400V 50Hz

Fresh water line: Soft cold water 0-3 °dH



© MEIKO 2016

Sample illustration

### Technical data

Rack capacity/h (theoretical)	60 / 40 / 17 racks/h
Programme cycle time *	60 / 90 / 210 s
Rack dimension	500 x 500 mm (540 x 500)
Entry height	440 mm
Dimensions (W x Hmin x D)	635 ( 687) x 1470 x 750 (850) mm (with hood rod)
Electrical feeding cable	3-phase current 3N PE 400V 50Hz* nominal capacity: 12.9 kW max. rated current: 23.1 A
Local fuse protection	32 A
Protection class of the machine	IP X4
Equipment	Automatic program start MIKE control Infrared interface for wireless communication Boiler safety device Automatic self-cleaning when tank is drained
Fresh water supply	Minimum flow pressure 250 kPa / 2.5 bar in front of solenoid valve Maximum pressure: 500 kPa / 5.0 bar Max. supply water temperature 60 °C
Flow rate	min. 0.3 l/s at 250 kPa/2.5 bar flow pressure
Final rinse water quantity	3 liters/cycle
Boiler	Contents: 9 l Heater: 12.00 kW Temperature: 83 °C Tank / boiler locked

# Technical data sheet

<b>Wash tank</b>	Filling: 22 l Heater: 2.00 kW Temperature: 60 °C
<b>Wash pump</b>	Performance: 0.75 kW
<b>Dosing of rinse aid</b>	Potential free terminals (changeable to 230V) for local dosing system
<b>Detergent dosage</b>	Potential free terminals (changeable to 230V) for local dosing system
<b>Material</b>	Cladding: 1.4301 Wash tank: 1.4301 Boiler: 1.4404
<b>Heat emission</b>	for 20 programme cycles/h total: 2.1 kW perceptible: 1.4 kW latent: 0.7 kW
<b>Ventilation flow rate</b>	540 m³/h
<b>Steam emission</b>	1.0 kg/h
<b>Emission sound pressure level at the workplace (LpA)</b>	65 dB
<b>Net / gross weight</b>	98.0 kg / 130.0 kg (standard packaging)
<b>Packaging dimensions (W x H x D)</b>	730 x 1700 x 870 mm (standard packaging)

**\*Note:**

Electrical equipment suitable for supply voltage:

3N PE 400 V 50 HZ (3N PE 380-415 V 50 Hz)

1N PE 230 V 50 HZ (1N PE 220-240 V 50 Hz)

\* Programme cycle time depending on temperature of feeding water:

Prolongation of wash cycle with cold water connection